



Dust Collection Non Woven Bags
Sintered Multilayer Wiremesh Bags
Designer-Manufacturer-Exporter-Supplier





Dust Collection Non Woven Bag

Filter bags are manufactured for achieving optimum filtration performance. They are made from carefully selected media. Various types of media are used such as needle felt, monofilament and multi-filament. They are effective in reducing dust emission levels as per requirement of industries. These bags are placed in dust collector with supporting filter cages. Contaminated air takes path of outside to inside filtration. All solid contaminants get deposited at outer surface & clean air / gas passes through top chamber. Particles retained at the outer surface of media get collected at the bottom of dust collector with the help of shaking mechanism or pulse jetting mechanism.

Features & Benefits

- Highly efficient filtration level
- Depth type filtration
- Wide range of chemically compatible media
- High temperature resistance
- High flow efficiency
- High air to cloth ratio
- Various coatings are available

Technical Specifications

Filter media

- Non woven needle felt polyester
- Non woven needle felt polypropylene
- Aramide / Nomex / Conex
- Homopolymer Polyacrylonitrile
- Polyacrylic
- PTFE
- P84
- PPS / Ryton

Available coating & treatment

- Silicone coating
- Antistatic treatment with carbon fiber
- Antistatic treatment with copper wire
- Antistatic treatment with stainless steel fiber
- Water & oil repellent
- PTFE coating
- PTFE laminated

Sizes

- Customized sizes are available in cylindrical tube bags & pocket type bags

Configurations

- Snap band type
- Flange collar type
- Rubber cord type
- Customized

Applications

- | | |
|--|--|
| <ul style="list-style-type: none">• Pharmaceuticals• Steel & Power• Powder coating• Shot Blasting | <ul style="list-style-type: none">• Cement• Chemicals• Metals & Minerals• Paints & Pigments |
|--|--|

Sintered Multilayer Wiremesh Bag

Sintered multilayer wire mesh bags are designed for high temp Application of Industries. It can be used for high temperature up to 480°C. It has one standard combination of 5 Layers sintered wire mesh made from stainless steel which is brought together through vacuum sinter, compression and rolling and made into a kind of porous material.

Features & Benefits

- Large filtration area, from 1 Micron to 100 Micron for absolute filtration
- Steady filter rating, as it has two protective layers and sinter arts, the mesh of the filter layer is not easy to change
- High mechanical strength & excellent resistance to pressure due to fourth and fifth layers reinforced
- Easy to wash, specially back washing
- Heat resistance , Heat resistance up to 480°C
- Corrosion resistance
- Tractability, suit to cut, punching, wrap





Designed By: e-brandstudio.com

Filter Concept Pvt. Ltd.

(An ISO 9001:2008, ISO 14001:2004, OHSAS 18001:2007 Certified Company)

Corporate Office

302, "Aalin", Opp.Gujarat Vidhyapith,
B/h. Jet Airways Office, Ashram Road, Ahmedabad - 14.
Gujarat, INDIA.

Phone : +91-79-2754 1602, 2754 0069, 3291 8518

Fax : +91-79-2754 0801

E-mail : info@filter-concept.com

Manufacturing Unit

A-6, Pushparaj Industrial Estate,
Nutan Mill Compound, B/h. City-Gold Theatre, Saraspur,
Ahmedabad-380018. Gujarat, INDIA.

Phone : +91 -79 -2220 1921, 2220 1292

Fax : +91-79-2220 1911

E-mail : factory@filter-concept.com